



# *Telstar<sup>®</sup> LyoBeta*

*R+D Freeze-Dryers*



## *LyoBeta series*



### *A Responsible Choice*

New demands in R+D centers are related to scale-up feasibility and quality of procedures and research methods. FDA investigators consider that transfer of technology from R+D departments to clinical trials and later commercial production is often carried out with lack of strictness and poor documentation practices. Therefore, they are emphasizing on the concept of cGMP as a means of quality control, comprising all practices in R+D and production processes.

The new **LyoBeta Series** lyophilizers are laboratory units that have been designed specifically for advanced research centers, keeping in mind that initial development of new drugs is one of the most critical issues for their final commercial success.



## *Design features*

The **LyoBeta** is a compact unit with castors, constructed in a steel stove-enamelled cabinet. The equipment is supplied fully assembled, including the vacuum and refrigerating system and all necessary elements, ready for operation after connecting to the utility services.

### *Efficient Design*

**THE DESIGN OF THIS UNIT OFFERS THE BEST CAPABILITIES FOR R+D ACTIVITIES.** LyoBeta has been equipped with the appropriate components, devices and sensors to control processing conditions: temperature, pressure and time. This allows defining the process variables to achieve adequate control and reproducibility.

The equipment includes brazed plate heat exchangers, that used in combination with other high quality components, **YIELDS COOLING AND HEATING RATES OF 1°C/MIN** the same as production freeze-dryers.

**OPTIMIZATION OF PROCESS RECIPES IS EASILY PERFORMED BY MEANS OF THE CHAMBER CONDENSER VALVE**, which allows for pressure rise testing and thermodynamic control. This valve also permits proceeding with the product loading and unloading without defrosting the condenser if it has not reached full capacity.

The refrigeration system is capable of reaching -80°C in the condenser and -60°C on the shelves. It only uses HFC gases, which are authorized for use both at the present and in the long term.

### *Flexibility of Use*

By using the stoppering device, the distance between the shelves can easily be modified, so **THE UNIT CAN BE ADAPTED TO DIFFERENT PRODUCT FILL VOLUMES, VIAL SIZES AND/OR VIAL TYPES.** Moreover, a lateral inlet port allows the connection of a three way valve manifold for the freeze-drying of CN 29/32 open flasks.




# The best *Solutions* for *Advanced Research* Center



## *High Quality and Superior Craftsmanship*

**THE CHAMBER AND SHELVES HAVE BEEN CONSTRUCTED WITH THE SAME PHILOSOPHY AS PRODUCTION UNITS.** They are made entirely from stainless steel AISI 316 L and they are fully accessible inside for cleaning purposes. The condenser, which is also made of AISI 316 L, has a rapid ice-defrosting device, which works by means of a group of external electrical resistors. Both the chamber and the condenser have transparent acrylic doors to facilitate viewing of the process.



## *Precise Control and Temperature Uniformity*

The thermal fluid circulates inside the sandwich type channels of the shelves. This allows product pre-freezing and later heating during sublimation phase. An additional shelf thermally balances the equipment. **THIS FEATURE FOR LABORATORY FREEZE-DRYERS GUARANTEES UNIFORM HEAT TRANSFER AT ALL THE SHELVES.**

Research lyophilizers often have the pressure sensors located on the vacuum line, reflecting the pressure of the line to the vacuum pump rather than in the chamber. The **LyoBeta** has the vacuum sensor in the chamber, which makes possible monitoring and control the pressure which comprises the environment where the product is exposed. **THIS ALLOWS STUDYING AND OBTAINING THE FINEST SCALE-UP RESULTS.**





# Control system

## Based on **PLC** and user Friendly **TOUCH-SCREEN**

One of the main new features of the **LyoBeta Series** freeze-dryers is the incorporation of a non-proprietary PLC, instead of the classic microprocessor, more commonly used in this type of equipment. This system, fully proven in the industrial models, **guarantees maximum reliability and reproducibility in the process**, totally adapting the equipment to cGMP.

The system allows control of the freeze-dryer functions via a graphic HMI (Human Machine Interface) user interface, which offers the following possibilities:

- Displaying of information on system elements (valves, motors, indicators, etc.)
- Receiving information from alarms
- Acting within the parameters of the freeze-dryer cycle
- Eliminating the possibility of error in operation
- Protecting the system from unauthorized use
- Recipes development
- Download info to USB key

The user interface presents information in an attractive and intelligible manner on a graphic 6,5" touch screen, through which different data screens can be accessed by means of touch zones.




Optionally, the equipment can be connected to different peripherals, such as a chart recorder, printer or PC. When connected to a PC, two possibilities for working in the Windows environment are offered:

### **LyoLogger**

A data logging programme which enables collection of data such as graphs, events, alarms and history (ASCII files) through a serial port.

### **LyoSuite™**

A SCADA software program together with a suite of tools designed specifically for scientific R+D studies. It enables designing, loading and storing recipes, generating reports, historics, lists of alarms. Compliant with 21 CFR part 11.



# Freeze-Drying Equipment

## Technical data

FEATURE	Unit	LyoBeta 3PS	LyoBeta 4PS	LyoBeta 5PS	LyoBeta 6PL
Number of shelves	ud	3+1	4+1	5+1	6+1
Shelves dimensions w x d	mm	338 x 450	338 x 450	338 x 450	338 x 450
	inches	13 x 17	13 x 17	13 x 17	13 x 17
Useable shelf area	m <sup>2</sup>	0.45	0.60	0.75	0.9
	sq. ft.	4.93	6.57	8.21	9.86
Clearance	mm	100	71	54	66
	inches	3.7	2.6	3.9	2.4
Shelf temperature range	°C	-60 a +80	-60 a +80	-60 a +80	-60 a +80
Condenser capacity	kg	30	30	30	30
	lb	66	66	66	66
Condenser capacity in 24 h	kg	18	18	18	24
	lb	39	39	39	52
Final condenser temperature	°C	<-80	<-80	<-80	<-80
Electric power	kW	8	8	8	9
Power supply	V/Hz	230/I/50/60	230/I/50/60	230/I/50/60	400/III/50/60
		(other under request)	(other under request)	(other under request)	(other under request)
Vacuum pump flow	m <sup>3</sup> /h	9	9	9	18
	cfm	5	5	5	10
Weight	kg	650	650	650	910
	lb	1430	1430	1430	2010
Dimensions	Width	(mm/inches)	1245/49	1245/49	1245/49
	Height	(mm/inches)	1974/77.7	1974/77.7	1974/77.7
	Depth	(mm/inches)	818/32.2	818/32.2	818/32.2

## Available options

- Vent filter
- Spacing devices for shelf clearance adjustment
- Sampling thief device
- Clean room configuration
- Side manifold
- Product support trays
- Modules for additional temperature probes (4, 8, 12)
- Dew point monitor

- Weighting System
- SCADA R+D lyophilization software - LyoSuite™
- IQ/OQ documentation service

Standard accessories included in **LyoBeta** equipment:

- Vial stoppering and spacing device
- Isolation valve chamber to condenser
- Microsuite software



**Headquarters**  
Av. Font i Sagué, 55  
08227 Terrassa (Spain)  
T. +34 937 361 600  
F. +34 937 861 380

**North America**  
1504 Grundy's Lane  
Bristol, PA 19007 (USA)  
T. +1 215 826 0770  
F. +1 215 826 0222

[www.telstar-lifesciences.com](http://www.telstar-lifesciences.com)

